

# Safety Data Sheet



according to OSHA Hazard Communication  
29 CFR Part 1910.1200

according to Regulation (EC)  
No. 1907/2006 Article 31

## Section 1. Identification

**Product Code:** 986453

**Product Name:** SB BLK CANADA 150VOC

**Product Type:** SB Paint

**Recommended Use:** Traffic Markings

**Supplied by:** Ennis-Flint  
A Traffic Safety Solutions Company  
115 Todd Court  
Thomasville, NC 27360  
T: 800.331.8118 (For Technical Inquiries)

**Emergency Telephone:** Chemtrec 1-800-424-9300

## Section 2. Hazard(s) identification

**EMERGENCY OVERVIEW:** Extremely Flammable! This product contains a component suspected of causing cancer. However, it is in a non-respirable form and inhalation is unlikely to occur from exposure. This classification is relevant when exposed to dust or powder form only (e.g. sanding, grinding). May cause fire. In use, may form flammable/explosive vapour-air mixture.

### Classification

#### Symbol(s) of Product



### Signal Word

Danger

### GHS Named Chemicals On Label

Ethylbenzene, Xylene, Carbon Black, Crystalline Silica, Quartz, Methanol, Acetone, Methyl Ethyl Ket

### GHS HAZARD STATEMENTS

Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Serious Eye Damage, category 1	H318	Causes serious eye damage.
Acute Toxicity, Inhalation, category 2	H330	Fatal if inhaled.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.
Carcinogenicity, category 2	H351	Suspected of causing cancer.
Reproductive Toxicity, category 1A	H360	May damage fertility or the unborn child. Classified Category 1A known human reproductive toxicant Category 1B presumed human reproductive toxicant. Irreversible effects such as structural malfunctions, embryo/foetal lethality, post natal functional deficiencies.

**GHS PRECAUTIONARY STATEMENTS**

P201	Obtain special instructions before use.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/.../ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P284	Wear respiratory protection.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P310	Immediately call a POISON CENTER or doctor/physician.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P362	Take off contaminated clothing and wash before reuse.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

**Section 3. Composition/Information on ingredients**

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Acetone	67-64-1	10-25	GHS02-GHS06	H225-319-330-336
Xylene	1330-20-7	2.5-10	GHS02-GHS05	H226-315-318
Chloroalkanes	61788-76-9	2.5-10		
Ethylbenzene	100-41-4	1.0-2.5	GHS02	H225
di(2-ethylhexyl) phthalate	117-81-7	0.1-1.0	GHS08	H360
Carbon Black	1333-86-4	0.1-1.0	GHS08	H351
Crystalline Silica, Quartz	14808-60-7	0.1-1.0	GHS08	H351-373
Methanol	67-56-1	< 5.0	GHS02-GHS06- GHS08	H225-302-319-330-370
Methyl Ethyl Ketoxime	96-29-7	0.1-1.0	GHS05-GHS07- GHS08	H302-317-318-351

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>EINECS No.</u>	<u>REACH Reg No.</u>	<u>M-Factors</u>
Acetone	67-64-1	200-662-2	not available	0
Xylene	1330-20-7	215-535-7	not available	0
Chloroalkanes	61788-76-9	NI	not available	0
Ethylbenzene	100-41-4	202-849-4	not available	0
di(2-ethylhexyl) phthalate	117-81-7	204-211-0	01-2119484611-38-XXXX	0
Carbon Black	1333-86-4	215-609-9	not available	0
Crystalline Silica, Quartz	14808-60-7	238-878-4	not available	0
Methanol	67-56-1	200-659-6	01-2119433307-44-XXXX	0
Methyl Ethyl Ketoxime	96-29-7	202-496-6	not available	0

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

**Section 4. First-aid measures**

**FIRST AID - INHALATION:** Move to fresh air. Give oxygen or artificial respiration if needed. Call a physician or poison control center immediately. Consult a physician if symptoms persist.

**FIRST AID - SKIN CONTACT:** Wash affected area immediately with soap and plenty of water. Remove contaminated clothing and launder before reuse. Consult a physician if symptoms persist.

**FIRST AID - EYE CONTACT:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult a

physician if symptoms persist.

**FIRST AID - INGESTION:** Do NOT induce vomiting. If conscious, rinse mouth and drink plenty of water. Never give anything by mouth to an unconscious person. Consult a physician.

## Section 5. Fire-fighting measures

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Material may polymerize explosively when involved in a fire. Runoff to sewer may create fire or explosion hazard. Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Vapors can spread along ground and collect in low or confined areas (sewers, basements, tanks). Water spray may reduce vapor, but may not prevent ignition in closed spaces.

**SPECIAL FIREFIGHTING PROCEDURES:** Flammable. Cool fire-exposed containers using water spray. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**EXTINGUISHING MEDIA:** Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

## Section 6. Accidental release measures

**ENVIRONMENTAL PRECAUTIONS:** Prevent entry into waterways, sewers, basements or confined areas. Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. A vapor suppressing foam may be used to reduce vapors. Use personal protective equipment. Ensure adequate ventilation. Dike far ahead of liquid spill for later disposal. Soak up with inert absorbent material. Take up mechanically. Keep in suitable and closed containers for disposal. Use clean non-sparking tools to collect absorbed material.

## Section 7. Handling and storage



**HANDLING:** Flammable liquid. Avoid heat, sparks and open flames. Ensure adequate ventilation. Avoid breathing vapor, mists or dust. Avoid contact with eyes, skin, and clothing. Wear appropriate personal protective equipment. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Observe good industrial hygiene practices. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use only in an area containing flame proof equipment.

**STORAGE:** Keep containers tightly closed in a cool, well-ventilated place. Store away from heat and sources of ignition. Keep in properly labeled containers.

## Section 8. Exposure controls/personal protection

### Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
Acetone	500 PPM	750 PPM	750 PPM	
Xylene	100 PPM	150 PPM	100 ppm	
Chloroalkanes				
Ethylbenzene	100 PPM	125 ppm	100 PPM	
di(2-ethylhexyl) phthalate	5 mg/m <sup>3</sup>		5 mg/m <sup>3</sup>	
Carbon Black	3.5 mg/m <sup>3</sup>		3.5 mg/m <sup>3</sup>	
Crystalline Silica, Quartz	0.025 mg/m <sup>3</sup>		0.05 mg/m <sup>3</sup>	
Methanol	200 PPM	250 PPM	200 PPM	
Methyl Ethyl Ketoxime				

<u>Name</u>	<u>Percentage</u>	<u>VME mg/m<sup>3</sup></u>	<u>VME ppm</u>	<u>OEL Nota</u>
Acetone	10-25	1210	500	1000 PPM
Xylene	2.5-10	220	50	100 ppm
Ethylbenzene	1.0-2.5	441	100	100 ppm
Carbon Black	< 1.0	3.5	0	3.5 mg/m <sup>3</sup>
Methanol	< 1.0	266	200	200 PPM

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation  
Sk = Skin Sensitizer N.E. = Not Established

### Personal Protection



**RESPIRATORY PROTECTION:** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.



**SKIN PROTECTION:** Protective gloves/clothing.



**EYE PROTECTION:** Tightly fitting safety goggles.



**OTHER PROTECTIVE EQUIPMENT:** Eyewash stations, safety showers, ventilation systems. Ventilation system should be explosion proof.



**HYGIENIC PRACTICES:** When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice.

## Section 9. Physical and chemical properties

<b>Appearance:</b>	Black	<b>Physical State:</b>	Liquid
<b>Odor:</b>	Solvent	<b>Odor Threshold:</b>	Not Established
<b>Density, g/cm<sup>3</sup>:</b>	1.490	<b>pH:</b>	No Information
<b>Freeze Point, °C:</b>	NI	<b>Viscosity:</b>	NI
<b>Solubility in Water:</b>	Insoluble	<b>Partition Coefficient, n-octanol/ water:</b>	NI
<b>Decomposition Temp., °C:</b>	NI		
<b>Boiling Point, °C:</b>	N.I.	<b>Explosive Limits, vol%:</b>	N.I.
<b>Combustibility:</b>	Supports Combustion	<b>Flash Point, °C:</b>	-18
<b>Evaporation Rate:</b>	Slower than Diethyl Ether	<b>Auto-ignition Temp., °C:</b>	NI
<b>Vapor Density:</b>	Heavier than air	<b>Vapor Pressure:</b>	NI

(See "Other information" Section for abbreviation legend)

## Section 10. Stability and reactivity

**STABILITY:** Stable under recommended storage conditions.

**CONDITIONS TO AVOID:** Dust formation. Heat, flames and sparks.

**INCOMPATIBILITY:** Strong acids. Chlorinated compounds. Strong oxidizing agents.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon oxides. Hydrocarbons. Carbon dioxide.

**HAZARDOUS POLYMERIZATION:** Hazardous polymerization does not occur.

## Section 11. Toxicological information



### Practical Experiences

**EFFECT OF OVEREXPOSURE - INHALATION:** May be harmful if inhaled. Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes). May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Sanding and grinding dust may be harmful if inhaled.

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Irritating to skin. Repeated exposure may cause skin dryness or cracking.

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** Irritating to eyes.

**EFFECT OF OVEREXPOSURE - INGESTION:** Ingestion may cause irritation to mucous membranes. May cause gastrointestinal irritation, nausea, vomiting, and diarrhea. May cause gastrointestinal disturbances with dizziness and central nervous system depression.

**EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS:** Ethylbenzene has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands. This product contains carbon black in a non-respirable form. Inhalation of carbon black is unlikely to occur from exposure to this product. Inhalation exposure to respirable levels of crystalline silica may cause respiratory impairment and lung damage. This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen. Inhalation, ingestion, or skin absorption of methanol can cause blindness.

### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name according to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Gas LC50</u>
67-64-1	Acetone	5800 mg/kg rat	7426 mg/kg guinea pig	21.05 PPM - 8 h rat
1330-20-7	Xylene	>2000 mg/kg	> 2000 mg/kg	>20001 ppm
61788-76-9	Chloroalkanes	> 2000 mg/kg	> 2000 mg/kg	>20001 ppm
100-41-4	Ethylbenzene	>2000 mg/kg	15,433 mg/kg rabbit	>20001 ppm
117-81-7	di(2-ethylhexyl) phthalate	30000 mg/kg rat	25000 mg/kg rabbit	>20001 ppm
1333-86-4	Carbon Black	>8000 mg/kg rat	>3000 mg/kg rabbit	>20001 ppm
14808-60-7	Crystalline Silica, Quartz	>2000 mg/kg	> 2000 mg/kg	>20001 ppm
67-56-1	Methanol	1187 -2769 mg/kg rat	17100 mg/kg rabbit	128.2 PPM - 4 h rat
96-29-7	Methyl Ethyl Ketoxime	930 mg/kg	> 2000 mg/kg	>20001 ppm

N.I. - No Information

## Section 12. Ecological information

**ECOLOGICAL INFORMATION:** The environmental impact of this product has not been fully investigated.

### Further Ecological Information

Contains the following ingredients which are classified as water dangerous according to EEC directive No. 76/464/EEC in percentages > 1%.

<u>CAS-No.</u>	<u>Name according to EEC</u>	<u>Bio. Conc. Factor (BCF)</u>	<u>Octanol-water par. Coeff (KOW)</u>
67-64-1	Acetone	3	-0.24
1330-20-7	Xylene	not available	not available
61788-76-9	Chloroalkanes	NI	NI
100-41-4	Ethylbenzene	0.67 -15.00	3.15
117-81-7	di(2-ethylhexyl) phthalate	118 - 817	not available
1333-86-4	Carbon Black	not available	not available
14808-60-7	Crystalline Silica, Quartz	not available	not available
67-56-1	Methanol	1	-0.77
96-29-7	Methyl Ethyl Ketoxime	0.5 - 5.8	not available

## Section 13. Disposal considerations



Product

**DISPOSAL METHOD:** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of contents/ container in accordance with the local/regional/national/international regulations. Do not re-use empty containers. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

European Waste Code: 080111 waste paint/var.w.org.solv/DS

Uncleaned Packaging

European Waste Code: 150110 packaging dangerous residuals

**Section 14. Transport information**

SPECIAL TRANSPORT PRECAUTIONS: No Information

**Road Transport**

UN Number:	UN1263
ADR/RID Class:	3
Packing Group:	2
Shipping Name:	Paint
Primary Shipping Hazard:	No Information
Road Tunnel Transport Code:	NI

**Sea Transport**

UN Number:	UN1263
IMDG/GGVSee Class:	3
EmS-No:	F-E, S-E
Packing Group:	2
Shipping Name:	Paint
Primary Shipping Hazard:	No Information
Marine Pollutant:	Not A Marine Pollutant
Shipping Hazard(Marine Pollutant):	No Information

**Air Transport**

UN Number:	UN1263
ICAO/IATA Class:	3
Packing Group:	2
Shipping Name:	Paint
Primary Shipping Hazard:	No Information

**Section 15. Regulatory information****U.S. Federal Regulations:****CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

**SARA SECTION 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
Xylene	1330-20-7
Ethylbenzene	100-41-4
di(2-ethylhexyl) phthalate	117-81-7
Methanol	67-56-1
Dinonylphenol (branched)	872-50-4

**TOXIC SUBSTANCES CONTROL ACT:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

<u>Chemical Name</u>	<u>CAS-No.</u>
Acetone	67-64-1
Xylene	1330-20-7
Chloroalkanes	61788-76-9
Ethylbenzene	100-41-4
di(2-ethylhexyl) phthalate	117-81-7
Carbon Black	1333-86-4
Crystalline Silica, Quartz	14808-60-7
Methanol	67-56-1
Methyl Ethyl Ketoxime	96-29-7
Bisphenol A Diglycidyl Ether	25085-99-8
Mineral Spirits (Stoddard Solvent)	8052-41-3
Dinonylphenol (branched)	872-50-4
Solvent Naphtha (Petroleum), Light Aromatic	64742-95-6
Lithium Chloride	7447-41-8

**U.S. State Regulations:****NEW JERSEY RIGHT-TO-KNOW:**

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
Calcium Carbonate	1317-65-3
Nepheline Syenite	37244-96-5
n-butyl methacrylate copolymer	9003-63-8

**PENNSYLVANIA RIGHT-TO-KNOW**

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS-No.</u>
Calcium Carbonate	1317-65-3
Nepheline Syenite	37244-96-5
n-butyl methacrylate copolymer	9003-63-8

**CALIFORNIA PROPOSITION 65 CARCINOGENS**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

<u>Chemical Name</u>	<u>CAS-No.</u>
Ethylbenzene	100-41-4
di(2-ethylhexyl) phthalate	117-81-7
Carbon Black	1333-86-4
Crystalline Silica, Quartz	14808-60-7

**CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

<u>Chemical Name</u>	<u>CAS-No.</u>
di(2-ethylhexyl) phthalate	117-81-7

**International Regulations: As follows -****CANADIAN WHMIS:**

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

**WHMIS Class:** B2, D2A, D2B

**Denmark****B-Value:** 0.000000**France****Storage Conditions:** No Information**Professional Illness Table:**

<u>CAS Number</u>	<u>Chemical Name</u>	<u>Professional Illness</u>
67-64-1	Acetone	not available
1330-20-7	Xylene	not available
61788-76-9	Chloroalkanes	NI
100-41-4	Ethylbenzene	not available
117-81-7	di(2-ethylhexyl) phthalate	not available
1333-86-4	Carbon Black	not available
14808-60-7	Crystalline Silica, Quartz	not available
67-56-1	Methanol	not available
96-29-7	Methyl Ethyl Ketoxime	not available

**Germany****VbF-Class:** No Information**WGK-class:** 3

**Remarks:** WGK 0 = in general not a water pollutant  
 WGK 1 = weak water pollutant  
 WGK 2 = water pollutant  
 WGK 3 = severe water pollutant

**Processing restrictions:\*****Incident Regulation:**

No Information

**Spain****Storage Conditions:** No Information**Switzerland****VOC-Value:** 22.58**United Kingdom****Storage Conditions:** No Information**Section 16. Other information, including date of preparation of the last revision****Revision Date:** 10/19/2016 **Supersedes Date:** 6/17/2016**Reason for revision:** Statement(s) Changed**Datasheet produced by:** Regulatory Department**HMIS Ratings:**

<b>Health:</b>	2	<b>Flammability:</b>	3	<b>Reactivity:</b>	0	<b>Personal Protection:</b>	X
----------------	---	----------------------	---	--------------------	---	-----------------------------	---

**NFPA Ratings:**

<b>Health:</b>	2	<b>Flammability:</b>	3	<b>Reactivity:</b>	0	<b>Hazards:</b>	None
----------------	---	----------------------	---	--------------------	---	-----------------	------

**Volatile Organic Compounds, gr/ltr:** 147**Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

H225 Highly flammable liquid and vapour.



H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.

**Icons for GHS Pictograms shown in Section 3 describing each ingredient:**

GHS02	
GHS05	
GHS06	
GHS07	
GHS08	

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed. Any use of the product not in conformance with this SDS or in combination with any other product or process is the responsibility of the user.